

ULTRA-FLO[®] LRO-20 BRACKISH WATER

Reverse Osmosis (RO) Membrane System



The 'Know-how' in Water Treatment



System includes:

- 1 x RO membrane module
- Electrical control panel
- Feed and Hi-Pressure Pumps
- 5µm Guard-Filters
- Manual & Electrical Solenoid Control Valve
- Pressure Gauges, Flow Meters
- Permeate Conductivity Meter
- System on Racking, PVC & Stainless Steel Piping
- C.I.P setup with Tank

LRO System & Operating Limit :

Recovery	75~90 %
Operating Temp	< 45° C
Operating Pressure	< 20 Bar
Electrical Power	1 x 230V/ 50Hz
Max. SDI (15min.)	< 5.0
pH range	3 – 10
Feed Max. Turbidity	< 1.0 NTU

Note: Any of the above mentioned component is subjected to change without prior notice.

Membrane Specifications :

Type	TFC (Thin Film Composite)
Material	PA (Polyamide)
Charge	Negative
Configuration	Spiral-Wound, FRP Wrapping
Membrane Size	Diameter 8" x Length 40"
Effective Area	400 sq ft/membrane
Flow Rate	0.8~1.0 m ³ /hr/membrane

Note: Selection of membrane will depend on the application
Flow rate depends on the type of feed water

Clean Water Tech Pte Ltd, 41Sungei Kadut Loop
Singapore 729509
Tel: +65 67905516
Fax: +65 67910788

